

Revision Date: 19.02.2025	
Date of last issue: -	

Version 1.0

Print Date 28.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikaflex[®]-403 Tank & Silo

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Ireland Ltd
		Sika House
		Ballymun Industrial Estate
		Dublin 11
Telephone	:	+353 1862 0709
E-mail address of person	:	EHS@UK.Sika.com
responsible for the SDS		

1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166 (available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word	:	Danger
Hazard statements	:	H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled.



Revision Date: 19.02.2025 Date of last issue: -	N	/ersion 1.0	Print Date 28.03.2025
Precautionary statements	: Prevention: P261 P284	Avoid breathing mist or vapour In case of inadequate ventilation atory protection.	
	Response:		
	P304 + P340	IF INHALED: Remove person keep comfortable for breathing	
	P342 + P311	If experiencing respiratory sym	

101211011	POISON CENTER/ doctor.
Disposal:	
P501	Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

4,4'-methylenediphenyl diisocyanate

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

> "As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Urea,N,N"-(methylenedi-4,1- phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72- XXXX	Aquatic Chronic 4; H413	>= 2,5 - < 5

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex[®]-403 Tank & Silo



Revision Date: 19.02.2025 Date of last issue: -

Version 1.0

of last issue: -			
4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 	>= 0,1 - < 0,5
		<pre>>= 5 % specific concentration limit STOT SE 3; H335 >= 5 %</pre>	
		specific concentration limit Skin Irrit. 2; H315 >= 5 %	
		specific concentration limit Resp. Sens. 1; H334 >= 0,1 %	
		Acute toxicity esti- mate	
		Acute inhalation tox- icity (dust/mist): 1,5 mg/l	
Alcohols, C11-14-iso-, C13-rich	68526-86-3 271-235-6 01-2119454259-32- XXXX	Skin Irrit. 2; H315 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0,1 - < 0,25
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikaflex[®]-403 Tank & Silo

ision Date: 19.02.2025 e of last issue: -		
Substances with a workplace ex	kposure limit :	
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5	>= 1 - < 2,5
	01-2119489379-17- XXXX	

SECTION 4: First aid measures

4.1 Description of first aid measures

	General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
	If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
	In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
	In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
	If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2	Most important symptoms and	d e	ffects, both acute and delayed
	Symptoms	:	Asthmatic appearance Allergic reactions See Section 11 for more detailed information on health effects and symptoms.
	Risks	:	sensitising effects
			May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.



Version 1.0

Print Date 28.03.2025

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox-
		ide/sand/foam/alcohol resistant foam/chemical powder for
		extinction.

5.2 Special hazards arising from the substance or mixture

nazaruous compusitori prou No	o hazardous combustion products are known
ucts	

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.

SECTION 6: Accidental release measures

	ve equipment and emergency procedures Use personal protective equipment. Deny access to unprotected persons.	
6.2 Environmental precautions Environmental precautions :	Do not flush into surface water or sanitary sewer system.	
 6.3 Methods and material for containment and cleaning up Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. 		
6.4 Reference to other sections For personal protection see sec	tion 8.	

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8).
		For personal protection see section 8.
		Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Sikaflex[®]-403 Tank & Silo



Revision Date: 19.02.2025 Date of last issue: -		Version 1.0	Print Date 28.03.2025
		Smoking, eating and drinking should be prohibit plication area. Follow standard hygiene measures when handli products	·
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.	
Hygiene measures	:	Handle in accordance with good industrial hygie practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the e	using do not
7.2 Conditions for safe storage,	inc	luding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-v place. Store in accordance with local regulations	
Further information on stor- age stability	:	: No decomposition if stored and applied as directed.	
7.3 Specific end use(s)			
Specific use(s)	:	Cleaning with aprotic polar solvents must be ave Consult most current local Product Data Sheet p use.	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 μm)	13463-67-7	OELV - 8 hrs (TWA) (Respira- ble dust)	4 mg/m3	IE OEL
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m3	IE OEL
4,4'-methylenediphenyl diisocyanate	101-68-8	OELV - 8 hrs (TWA)	0,005 ppm (NCO)	IE OEL
	Further information: Chemical agents which following expo may cause sensitisation of the respiratory tract and lead to ma, rhinitis or extrinsic allergic alveolitis			

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.



Version 1.0

Print Date 28.03.2025

Ensure adequate ventilation, especially in confined areas.

· · ·	-
Personal protective equipment	
Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
Environmental exposure contr	ols
	De net fluch inte curfece unter er coniter a courter outer

General advice

: Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	:	liquid paste various
Odour	:	slight

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex[®]-403 Tank & Silo



Revision Date: 19.02.2025 Date of last issue: -		Version 1.0	Print Date 28.03.2025
Melting point/ range / Freez- ing point	:	No data available	
Boiling point/boiling range	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or	exp	plosive limits	
Upper explosion limit / Up- per flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	> 100 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	Not applicable substance/mixture is non-soluble (in water)	
Viscosity		> 20,5 mm2/s (40 °C)	
Viscosity, kinematic	:	> 20,5 mm2/5 (40 °C)	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,01 hPa	
Density	:	ca. 1,20 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	



Version 1.0

Print Date 28.03.2025

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid	:	No data available
---------------------	---	-------------------

10.5 Incompatible materials

Materials to avoid : No data available
--

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 401
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg Method: OECD Test Guideline 402

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg	
		Method: OECD Test Guideline 401	

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex[®]-403 Tank & Silo



Revision Date: 19.02.2025 Date of last issue: -	Version 1.0	Print Date 28.03.2025
Acute inhalation toxicity :	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method	
Skin corrosion/irritation Not classified due to lack of data		
Serious eye damage/eye irritat Not classified due to lack of data		
Respiratory or skin sensitisation		
Skin sensitisation Not classified due to lack of data		
Respiratory sensitisation May cause allergy or asthma syr	nptoms or breathing difficulties if inhaled.	
Germ cell mutagenicity Not classified due to lack of data		
Carcinogenicity Not classified due to lack of data		
Reproductive toxicity Not classified due to lack of data		
STOT - single exposure Not classified due to lack of data		
STOT - repeated exposure Not classified due to lack of data		
Aspiration toxicity Not classified due to lack of data		
11.2 Information on other hazards		
Endocrine disrupting propertie	25	
Product: Assessment :	The substance/mixture does not contain comp ered to have endocrine disrupting properties at REACH Article 57(f) or Commission Delegated (EU) 2017/2100 or Commission Regulation (EU levels of 0.1% or higher.	ccording to I regulation



Version 1.0

Print Date 28.03.2025

SECTION 12: Ecological information

12.1 Toxicity

Components:

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l Exposure time: 72 h

Alcohols, C11-14-iso-, C13-rich:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 0,42 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia (water flea)): 0,71 mg/l Exposure time: 48 h

M-Factor (Acute aquatic tox- icity)	:	1	
iony)			

M-Factor (Chronic aquatic : 1 toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Sikaflex[®]-403 Tank & Silo



Revision Date: 19.02.2025 Date of last issue: -	Version 1.0	Print Date 28.03.2025
Assessment	: The substance/mixture does not c ered to have endocrine disrupting REACH Article 57(f) or Commission (EU) 2017/2100 or Commission R levels of 0.1% or higher.	properties according to on Delegated regulation
12.7 Other adverse effects		
Product:		
Additional ecological infor- mation	: There is no data available for this	product.
SECTION 13: Disposal consi	erations	
13.1 Waste treatment methods		
Product	: The generation of waste should be wherever possible.	

	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.	
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.	
	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.	
European Waste Catalogue	: 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances	
Contaminated packaging	15 01 10* packaging containing residues of or contaminated by dangerous substances	

SECTION 14: Transport information

14.1 UN number or ID number				
ADR	:	Not regulated as a dangerous good		
IMDG	:	Not regulated as a dangerous good		
ΙΑΤΑ	:	Not regulated as a dangerous good		
14.2 UN proper shipping name				
ADR	:	Not regulated as a dangerous good		
IMDG	:	Not regulated as a dangerous good		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex[®]-403 Tank & Silo



Revision Date: 19.02.2025 Date of last issue: -	Version 1.0	Print Date 28.03.20
ΙΑΤΑ	: Not regulated as a dangerous good	
14.3 Transport hazard class(es)	
ADR	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
4.4 Packing group		
ADR	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
IATA (Cargo)	: Not regulated as a dangerous good	
IATA (Passenger)	: Not regulated as a dangerous good	
 4.5 Environmental hazards Not regulated as a danger 4.6 Special precautions for 	-	
Not applicable		
Not applicable for product SECTION 15: Regulatory in 15.1 Safety, health and enviro	nformation	
International Chemical We Schedules of Toxic Chemi	apons Convention (CWC) : Not applicable cals and Precursors	
REACH Information:	All substances contained in our Products a - registered by our upstream suppliers, an - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.	
	ain dangerous substances, lowing entries	estriction for the fol- should be considered:

mixtures and articles (Annex XVII)

Concern for Authorisation (Article 59).

REACH - Candidate List of Substances of Very High

: None of the components are listed

Number on list 3

Number on list 75 Banned and/or restricted

(=> 0.1 %).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex[®]-403 Tank & Silo



Revision Date: 19.02.2025 Date of last issue: -	Version 1.0	Print Date 28.03.2025
REACH - List of substances sub (Annex XIV)	ject to authorisation : Not applicable	
Regulation (EU) No 2024/590 o plete the ozone layer	n substances that de- : Not applicable	
Regulation (EU) 2019/1021 on p tants (recast)	persistent organic pollu- : Not applicable	
Regulation (EU) No 649/2012 o ment and the Council concernin of dangerous chemicals		
Seveso III: Directive 2012/18/EU jor-accident hazards involving d	J of the European Parliament and of the Council o angerous substances. Not applicable	on the control of ma-
Volatile organic compounds	Law on the incentive tax for volatile organic co (VOCV) Volatile organic compounds (VOC) content: < no VOC duties	
	Directive 2010/75/EU of 24 November 2010 or livestock rearing emissions (integrated pollutio and control) Volatile organic compounds (VOC) content: <	n prevention
If other regulatory information a Sheet, then it is described in the	oplies that is not already provided elsewhere in th s subsection.	e Safety Data
Health, safety and environ-	: Environmental Protection Act 1990 & Subsidia	ry Regulations

Health, safety and environ- mental regulation/legislation specific for the substance or mixture:	:	Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH) May be subject to the Control of Major Accident Hazards Regulations (COMAH) and amendments
		Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006, as amended by Commission Regula-
tion (EU) 2020/878
Sikaflex [®] -403 Tank & Silo



Version 1.0

Print Date 28.03.2025

SECTION 16: Other information

Full text of H-Statements		
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319		Causes serious eye irritation.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul-
11554	•	ties if inhaled.
L1225		
H335	÷	May cause respiratory irritation.
H351	:	Suspected of causing cancer.
H373	:	May cause damage to organs through prolonged or repeated
		exposure if inhaled.
H400	:	Very toxic to aquatic life.
H411	:	Toxic to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.
Full text of other abbreviatio	ons	
Acute Tox.		Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
	:	
Aquatic Chronic	·	Long-term (chronic) aquatic hazard
Carc.	:	Carcinogenicity
Eye Irrit.	:	Eye irritation
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
IE OEL	:	Ireland. List of Chemical Agents and Carcinogens with Occu-
		pational Exposure Limit Values - Code of Practice, Schedule 1
		and 2
IE OEL / OELV - 8 hrs (TWA)	:	Occupational exposure limit value (8-hour reference period)
ADR		European Agreement concerning the International Carriage of
, lett	·	Dangerous Goods by Road
CAS		Chemical Abstracts Service
	:	
DNEL	÷	Derived no-effect level
EC50	÷	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
	•	air that kills 50% of the test animals during the observation
		period)
MARPOL		International Convention for the Prevention of Pollution from
	·	
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration

Sikaflex[®]-403 Tank & Silo



Revision Date: 19.02.2025 Date of last issue: -	Version 1.0	Print Date 28.03.2025
REACH	: Regulation (EC) No 1907/2006 of the l and of the Council of 18 December 20 istration, Evaluation, Authorisation and cals (REACH), establishing a Europea	06 concerning the Reg- I Restriction of Chemi-
SVHC	: Substances of Very High Concern	
vPvB	: Very persistent and very bioaccumulat	ive
Further information		

Classification of the mixture:		Classification procedure:
Resp. Sens. 1	H334	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

IE / EN